

ULTRASONIC

SENSOR	MEASUREMENT RANGE	EXPOSED MATERIALS	MOUNTING
PZ32T	32 ft. / 10 m	PVC and Teflon	¾" NPT
PZ32TE	32 ft. / 10 m	all Teflon	¾" NPT
PZ34	32 ft. / 10 m	PVC	¾" NPT
PZ34TxF	32 ft. / 10 m	all Teflon face	Flange mount
PZ12	12 ft. / 3.66 m	PVC	¾" NPT
PZ12-LP	12 ft. / 3.66 m	PVC	SS mounting bracket
PZ12TxF	12 ft. / 3.66 m	all Teflon face	Flange mount
PZ52T	50 ft. / 15.6 m	PVC and Teflon	¾" NPT
PZ80	80 ft. / 25 m	PVC	1" NPT

PRESSURE

SENSOR	MEASUREMENT RANGE	EXPOSED MATERIALS	MOUNTING
PSxxS	5 – 70 psi / 0.3 – 5.0 bar	303 SS, polyurethane	Cable mount
PSxxT	5 – 75 psi / 0.3 – 5.2 bar	316 & 15-5 SS	¼" NPT

MISCELLANEOUS

MODEL	DESCRIPTION
SBMS	Submergence Shield for PZ32T, PZ32TE, PZ34 or PZ12 ultrasonic level sensors