

Automatic Flow Switch

Senses Flow/No-Flow from Outside a Pipe

Microphone Flow Switch

Model MFS100

Controls Liquids
and pneumatically
conveyed Solids



**Strap-on Sensor installs on the Outside of any Pipe to
Activate a Relay for Automatic Control or Alarm**

Low-cost Control

Use this simple, low-cost Microphone Switch on any size pipe to activate an alarm, pump or valve in flow no-flow conditions.

The MFS100 Microphone Switch reacts to noise inside the pipe caused by the flow of liquids or flowable solids. Noise from the flow is detected and amplified to operate the control relay. The absence of noise in no-flow conditions return the relay to stand-by position.

Installs in Minutes

The Microphone Switch sensor is mounted on the outside of any pipe with a simple clamp. No contact is made with the moving material, there is no obstruction to flow and no holes are drilled in the pipe.

Greyline
instruments inc.

RELIABLE MEASUREMENT AND CONTROL

Quick and Simple Flow Control

MFS100 Microphone Flow Switch Installs in Minutes

Use this low-cost Microphone Flow Switch on the outside of any pipe when controls or alarms are required to operate automatically when flow starts or stops.

Because the Microphone Flow Switch uses a strap-on sensor, there is no interference from build-up, caustic or acid solutions, or solids carried in the liquid. Recommended for all liquids and pneumatically conveyed solids.

The MFS100 can be field-adjusted to switch at the noise/flow level required in each application. Avoid installation in high noise or high vibration locations.

Specifications and Features

Shipping Weight: 4 lbs. (1.8 kg)
Enclosure: Watertight dust tight NEMA4X (IP66) fiberglass with clear Face
Power Input: 115VAC 50/60Hz (2 watts)
Relay Contacts: 5 ampere SPDT
Connections: Screw-type Terminal strips
Indication: Power and Relay condition LED's
Sensitivity: adjustable to flow noise level in each application
Electronics Operating Temperature: -5° to 140°F (-20° to 60°C)
Sensor: Strap-on, stainless steel housing
Sensor Operating Temperature: -20° to 200°F (-30° to 94°C)
Sensor Cable: 5 ft (1.5 m) shielded coaxial cable
Pipe Diameter: Recommended for Pipes greater than ¼" (6.5 mm) OD

Options

230VAC 50/60Hz Power Input
24VDC Power Input
Extended Sensor Cable: 20 ft (6 m) length shielded coaxial cable
Adjustable Stainless steel Sensor mounting clamps
Enclosure Heater, thermostatically controlled

How to Order

Contact a Greyline sales representative in your area or phone one of our sales engineers. Describe your requirements and receive our prompt quotation.

Applications Support

Take advantage of Greyline's applications experience. Phone toll free 1-888-473-9546 for advice and information on applications, installation or service for Greyline instruments.

No Risk Appraisal

The Greyline MFS100 Microphone Flow Switch must meet your requirements. Discuss your application with a Greyline representative to arrange a 30-day trial.

The Greyline Guarantee

Quality of Materials and Workmanship - Each instrument manufactured by Greyline is warranted against defects in materials and workmanship for a period of one year from date of purchase. Refer to our limited warranty included with each product.

Greyline
instruments inc.

RELIABLE MEASUREMENT AND CONTROL

Canada: 16456 Sixsmith Dr., Long Sault, Ont. K0C 1P0
Tel: 613-938-8956 / 888-473-9546 Fax: 613-938-4857
USA: 407 County Route 46, Massena NY 13662
Tel: 315-788-9500 / 888-473-9546 Fax: 315-764-0419
Internet: www.greyline.com E-mail: info@greyline.com